CAMSHELVING® ELEMENTS SERIES



- State-of-the-art, composite material, strong as steel
- Designed for all areas of foodservice operations
- Resistant to moisture; won't rust or corrode shelving for life
- Impervious to moisture, salt and chemicals
- Won't peel, dent or warp; remains rust-free
- Ideal for use in cold, hot, wet and dry environments
- Easy to clean, dishwasher safe, removable shelf plates are embedded with Camguard* antimicrobial protection
- Lifetime warranty against rust and corrosion



4-SHELF STARTER UNITS

Each starter unit includes instruction manual. Assembly required.

ESU183672	18" x 36" x 72"
ESU184872	18" x 48" x 72"
ESU186072	18" x 60" x 72"
ESU243672	24" x 36" x 72"
ESU244872	24" x 48" x 72"
ESU246072	24" x 60" x 72"



WEIGHT CAPACITY

	Traverse Length	Weight Bearing Capacity Per Shelf Per Unit	
Single Unit	36" - 48"	800 lb	3200 lbs.
(4 shelves)	910 mm - 1220 mm	363 KG	1451 KG
Single Unit	54" - 78"	600 lbs.	2400 lbs.
(4 shelves)	1380 mm - 1980 mm	272 KG	1089 KG
Dunnage Stand	54" - 78" 1380 mm - 1980 mm bottom shelf only	1000 lbs. 454 KG	_
Corner Unit	36" - 48"	400 lbs.	1600 lbs.
(attached)	910 mm - 1220 mm	181 KG	726 KG
Mobile Unit	36" - 48" 910 mm - 1220 mm	-	750 lbs. 340 KG

- Dunnage Stands are recommended for traverses 54" (1380 mm) or longer
- Corner Connectors are recommended for use on traverses 48" (1220 mm) or less
- Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Elements unit is 750 lbs (340 KG)

COMPONENT PARTS AVAILABLE



Additional parts available. Call customer service for more information.

Camshelving Elements Series is available in configurations to fit every need. Other sizes and heights are available upon request, contact customer service.

CUSTOM CONFIGURATIONS



Mobile Unit



Starter Unit + Add-On Unit



Starter Unit + Corner Unit

U-Shaped Unit



TOLL FREE: (800) 852-2806